

3.0V, Clipped Sine, SMD TCXO/VCTCXO



Model: FOX307H

RoHS Compliant / Pb Free

Rev. 6/10/2009

Page 1 of 1

http://www.foxonline.com/need_a_sample.htm

Need a Sample®

FEATURES

- 3.0V Operation
- 1.9mm Height Max
- Clipped Sine Output
- Tape and Reel (2,000 pcs. STD)

Discontinued

• PART NUMBER SELECTION [Learn More](#) - Internet Required

Part Number	Model Number	Frequency Stability	Operating Temperature (°C)	Frequency Range (MHz)
483-Frequency-xxxxx	FOX307H	see table	-20 ~ +75	10.000 ~ 26.000

• ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency Range (Fo)	10.000 ~ 26.000 MHz
Temperature Range	
Operating (T _{OPR})	-20°C ~ +75°C
Storage (T _{STG})	-40°C ~ +85°C
Supply Voltage (V _{DD})	3.0V ± 5%
Input Current (I _{DD})	2.0mA
Frequency Stability	
Over Temperature Range	±2.5PPM
Over Supply Voltage Change (3.0V ± 5%)	±0.3PPM
Over Load Change (10 _z // 10pF) ±10%	±0.3PPM
Voltage Control ¹ (1.5V ± 1.0V)	±5.0 ~ ±15.0PPM
Output Waveform (Clipped Sine)	
Peak-to-Peak Level (V _{p-p})	0.8V Min
Output Load	10kΩ // 10pF ±10%
Aging per year	±1.0PPM

¹ For proper operation, a control voltage (V_c) must be applied to pin 1. All specifications subject to change without notice.

