

THE WORLD LEADER FOR EREQUENCY CONTROL COLUMN

Fox Electronics Headquarters 5570 Enterprise Parkway Fort Myers, FL. 33905 USA Tel: 888-GET-2-FOX Outside US: +1.239.693.0099 Fax:+1.239.693.1554 Fox Electronics EMEA 14 Banks Road Biggleswade, Bedfordshire SG18 0DY, United Kingdom Tel/Fax: +44,1767,312632 Fox Electronics Asia 4/F Gold & Silver Commercial Bldg. 12-18 Mercer St. Central, Hong Kong Tel: +852.2854.4285 Fax: +852.2854.4282 Fox Electronics Japan 3-28-6-1A Yoyogi Shibuya-ku, Tokyo 151 Japan Tel: +81.3.3374.2079 Fax: +81.3.3377.5221

Product Change Notification

PCN Publish Date: 05/10/2006

PCN#: 249

Change Title: Product End of Life (EOL)

Products Affected: FX325B: 3.2mm X 2.5mm X 0.8mm, Resin Sealed SMD crystal

FX425A: 4.0mm X 2.5mm X 0.8mm, Resin Sealed SMD crystal

Description of Change to the Customer: In an effort to streamline our crystal product line, Fox Electronics will be discontinuing the above products.

Recommended substitutions:

Discontinued	Recommended Substitution
Product	
FX325B	FX325BS http://www.foxonline.com/pdfs/fx325bs.pdf
FX425A	FX425B http://www.foxonline.com/pdfs/fx425B.pdf

The seal method for the recommended substitutions is seam seal.

The most significant difference is the package height for both products is 0.1mm less (due to changing from resin seal to seam seal).

Also, the chamfered pad for the FX425B is now pad #2 instead of pad #1

(Note: We recommend a sample be evaluated in all applications before making a substitution.)

Schedule of Change: A last time buy date is scheduled for Sept. 29, 2006.

A last time ship date is scheduled for Dec. 29, 2006.

Customer Impact and Response: We sincerely hope this product discontinuance will have minimal impact on our customers. If you have any questions or need assistance in determining a suitable substitution, please email Fox Technical Support at www.foxonline.com/email.htm or call 239-693-0099.